

# Cartridge Filter **CF SERIES**

COMPACT AND LIGHTWEIGHT  
For residential pool and spa



AquaIntegral<sup>®</sup>  
Agua para el futuro

UV resistant tank

Max Operating Pressure

250kPa/36psi(2.5bar)

Max Temperature

40°C (104°F)

**Pool & Spa Equipment**

**e Emaux**  
water technology

[www.emauxgroup.com](http://www.emauxgroup.com)

# CF Series Cartridge Filter

comes with a UV resistant tank and a heavy duty ring-lock lid which allows easy cleaning and replacement of the cartridge element. A screw type air bleed valve releases trapped air inside the filter tank. The high quality oil-filled pressure gauge provides an easy overview of the operating pressure.

## Product Information:


Code	Model	Filter Area (m <sup>2</sup> )	Valve Connections	Max Flow Rate	A mm	B mm	C mm
88060101	CF25	2.25	1.5" / 50mm	92lpm 5.5m <sup>3</sup> /h	445	387	225
88060102	CF50	4.63	1.5" / 50mm	190lpm 11.4m <sup>3</sup> /h	625	567	225
88060103	CF75	7.00	1.5" / 50mm	283lpm 17.0m <sup>3</sup> /h	805	747	225
88060104	CF100	9.40	2.0" / 63mm	382lpm 22.9m <sup>3</sup> /h	985	927	225
88060105	CF150	13.72	2.0" / 63mm	555lpm 33.4m <sup>3</sup> /h	1165	1107	225
88060106	CF200	16.82	2.0" / 63mm	680lpm 40.9m <sup>3</sup> /h	1345	1287	225



- CF Series Filter is equipped with :
1. universal standard of union connection
  2. pressure gauge
  3. cartridge filter element

## Cartridge Filter Element:

Code	Model	D mm	E mm	Micron $\mu$ m	Fold Number
88270101	CF25-CE	Ø183	184.5	≥15	150
88270102	CF50-CE	Ø183	364.5	≥15	150
88270103	CF75-CE	Ø183	544.5	≥15	150
88270104	CF100-CE	Ø183	724.5	≥15	150
88270105	CF150-CE	Ø183	904.5	≥15	175
88270106	CF200-CE	Ø183	544.5 x 2	≥15	180



## EMAUX WATER TECHNOLOGY CO., LTD

ADDRESS: Flat A-D, 20/F., Kai Bo 22, 22 Wing Kin Road,  
Kwai Chung, Hong Kong  
PHONE +852 2832 9880  
www.emauxgroup.com

Pool & Spa Equipment

 YOUR PREMIER SUPPLIER

Available from:

ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE  
© 2021 EMAUX WATER TECHNOLOGY CO., LTD. ALL RIGHTS RESERVED.