



We Build Better.®

SwimClear™

Single-Element Cartridge Filters

**LOWEST IN HEAD LOSS,
HIGHEST IN EFFICIENCY**



Aqua Integral®
Agua para el futuro

EXPERT LINE®



ONLY FROM POOL PROS



3+ YEAR PARTS & LABOR WARRANTIES*

*When sold by a Totally Hayward® Partner. Exclusions, other terms and conditions may apply — visit hayward.com/expert for details.



INCOMPARABLE EFFICIENCY

SwimClear™ filters are simply the most efficient single-element cartridge filters ever produced. Designed for greater hydraulic efficiency, they boast the industry's lowest head loss—saving pool owners more energy and money.



QUICK & EASY MAINTENANCE

A recessed pressure gauge and manual air relief allow for easy access to SwimClear's head assembly while also sealing the filter against contamination. And with the lowest body height on the market, cleaning and changing filter cartridges is easier than ever.



SIMPLE INSTALLATION

With 2" x 2½" union connections, SwimClear is quick and easy to retrofit in virtually any application. An Easy-Lok™ ring design and ergonomic handles offer confident filter handling while preventing contact with fiberglass-based surfaces.

SWIMCLEAR CARTRIDGE FILTERS

Filter Type	Cartridge element: 100 ft² / 150 ft² / 200 ft² (9.29 m² / 13.94 m² / 18.58 m²)
Filter Tank	High-strength, injection-molded, glass-reinforced copolymer
Filter Element	Reinforced polyester
Performance Range	100 to 120 GPM, 379 to 455 LPM
Union Connections	2" x 2 ½"
Dimensions	C100S: 30½" H x 18¼" W (775 mm x 464 mm)**
	C150S: 33¾" H x 18¼" W (857 mm x 464 mm)**
	C200S: 38¾" H x 18¼" W (984 mm x 464 mm)**



FILTER PERFORMANCE DATA

MODEL NUMBER	EFFECTIVE FILTRATION AREA	DESIGN FLOW RATE***	TURNOVER		CLEARANCE FOR HEAD REMOVAL	CTN. WEIGHT	
			8 HOURS	10 HOURS			
Residential	C100S	100 ft² / 9.29 m²	100 GPM / 379 LPM	48,000 gal / 182 kl	60,000 gal / 227 kl	12"	33 lbs.
	C150S	150 ft² / 13.94 m²	120 GPM / 455 LPM	57,600 gal / 218 kl	72,000 gal / 273 kl	15"	37 lbs.
	C200S	200 ft² / 18.58 m²	120 GPM / 455 LPM	57,600 gal / 218 kl	72,000 gal / 273 kl	18"	40 lbs.
Public	C100S	100 ft² / 9.29 m²	38 GPM / 142 LPM	18,240 gal / 68 kl	22,800 gal / 85 kl	12"	33 lbs.
	C150S	150 ft² / 13.94 m²	56 GPM / 213 LPM	26,880 gal / 102 kl	33,600 gal / 128 kl	15"	37 lbs.
	C200S	200 ft² / 18.58 m²	75 GPM / 284 LPM	36,000 gal / 136 kl	45,000 gal / 170 kl	18"	40 lbs.

Agua Integral®
Agua para el futuro

*When sold by a Totally Hayward® partner. Exclusions, other terms and conditions may apply — visit hayward.com/expert for details.

**Based on NSF recommended rate for commercial use at .375 GPM/ft²

***Determined by pump size and piping system hydraulics; 2" piping is recommended for flow rates equal to or greater than 90 GPM (341 LPM). Hayward doesn't recommend flow rates above 150 GPM.

» hayward.com » 1-888-HAYWARD

SwimClear Filters are listed by:

Pumps » Filters » Heaters » Sanitization » Automation » Lighting » Water Features » Cleaners » Safety